# P/N: FACM22BL-123Y1R8

RoHS

PAIRUI
www.fuantronics.net

## Outline Dimensions(Unit:mm)




Orthographic view

Side view




Top view




Bottom view




Winding Construction

## Electronical Schematic




## Recommended Soldering Temperature Graph.




| | Standard Profile | Standard Profile |
|---|---|---|
| Pre-heating | 150~180°C,90s±30s | |
| Heating | above 220°C,30s-60s | above 240°C,30s Max |
| Peak temperature | 245°C±3°C | 260°C,10s |
| Cycle of reflow | 2 times | 2 times |

## Electrical Characteristics(at 25°C)

Inductance : L1-4=2-3= 12mH Min,at 10KHz,0.1V.
Rated current: 1.80Amps.
D.C.Resistance : 1-4= 0.200 ohms Typ.
2-3= 0.200 ohms Typ.
Turns Ratio : Coil:Coil= 1:1±2%,at 20KHz,1V.
Hipot : Coil-Coil : 1500VAC/5mA/2Second.

## List of UL Certificate:

| Part Name | Mat'l Description | Supplier | UL Number |
|---|---|---|---|
| Base | Base-026/T375J | Chang Chun Plastics Co Ltd | E59481 |
| Copper wire | 2UEW-F/155C | Elektrisola Hangzhou Co Ltd | E258243 |
| Core | Ferrite core(Green) | Su Zhou Tian Ming Magnetic | N/A |
| Epoxy | E-500 | DongGuan Eatto Electronic Material Co Ltd | E218090 |
| Spacer | 2.00mm/FR-4 | Kingboard Laminates Holdings Ltd | E123995 |

| REV | DESCRIPTION | APPD | DATE |
|---|---|---|---|
| | | | |
| | | | |
| | | | |


Tianchang Fuan Electronic Co Ltd
www.fuantronics.net
TEL: +86-550-7814888
FAX:+86-550-7831133


Tolerances unless otherwise specified:
(.X)±0.50 (.XX)±0.25
Unit of measurement: mm

Make: Qiumei.Liu
Checked: Beson. zhan
Approved: Anson. zhan

**DRAWING TITLE**
CURRENT-COMPENSATED RING CORE DOUBLE CHOKES

Material Number: A31CM022S550

Customer P/N:
Document/Rev: 00
Specification Sheet: 1 of 1
Date of Recognition: Jan./02/2020


PAIRUI
SIMPLE SPEC FOR SELECTION